



Item No.	Part name	Material
1	Cable	
2	Motor protector	
3	Bearing house	Cast iron
4	Bearing	Ball Bearing
5	Motor body	Cast iron
6	Stator	
7	Rotor	
8	Bearing house	Cast iron
9	Oil seal bracket	
10	Plate	Cast iron
11	Pump body	Cast iron
12	Impeller	Cast iron
13	End stand	Cast iron
14	Hose coupling	Cast iron
15	Mechanical seal	Sic-sic/carbon ceramics
16	Up-cover	Cast iron
17	Plate	Cast iron
18	Bearing house	Cast iron
19	Patch board	
20	handle	Steel
21	shaft	AISI 1045

WQ ATIKSU POMPALARI

13-45 m

28-600 m³/h



UYGULAMALAR

- Belediye projeleri,
- Endüstriyel binalar,
- Maden ve İnşaat mühendisliği uygulamalar

Model	Voltage v	Motor power		Outlet inch	Guide Rial Fitting	Max.Flow m ³ /h	Max.Head m	Speed r.p.m	Impeller passage mm	N.W kg	Packing dimension mm
		Kw	HP								
50WQ10-10-0.75F	220	0.75	1,1	2	/	28	13	2860	25	19	510x230x270
65WQ15-15-1.5	380	1.5	2	2.5	/	35	20	2860	25	25	520x230x280
50WQ15-20-2.2	380	2.2	3	2	50-50	38	23	2860	25	44	680x250x310
65WQ25-17-2.2	380	2.2	3	2.5	65-65	44	22	2860	25	44	680x250x310
50WQ15-26-3	380	3	4	2	50-50	47	29	2860	25	50	700x270x340
65WQ25-22-3	380	3	4	2.5	65-65	55	26	2860	30	50	700x250x310
65WQ25-28-4	380	4	5.5	2.5	65-65	55	33	2860	30	62	800x290x360
80WQ40-18-4	380	4	5.5	3	80-80	80	24	2860	30	65	800x290x370
50WQ15-40-5.5	380	5.5	7.5	2	50-50	50	43	2860	20	73	810x320x340
80WQ30-30-5.5	380	5.5	7.5	3	80-80	47	37	2860	30	75	810x320x340
100WQ65-15-5.5	380	5.5	7.5	4	100-100A	108	25	2860	30	75	840x330x380
100WQ45-22-7.5	380	7.5	10	4	100-100A	90	31	2860	30	123	400x380x960
150WQ180-25-22	380	22	30	6	150-150	330	28	1450	50	324	500x610x1300
200WQ300-15-22	380	22	30	8	200-200	450	28	1450	50	324	500x610x1300

