

KOMPLE PASLANMAZ ÇELİK SANTRİFÜJ POMPALAR

MAX SU SICAKLIĞI : 70°C
MAX ORTAM SICAKLIĞI : 40°C
MAX EMİŞ : 6.5 m

Sıvıya Temas Eden Tüm Parçalar
AISI 304 PASLANMAZ ÇELİK

-20C'ye kadar dayanıklı mekanik keçeli



POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (cm)	H (cm)	DEBİ								
							m³/h	3	6	9	12	15	18	21	24
CA 50-32/3M	3	220	DN50	DN32	428	255	h(m)	30	29	27	26	24	22	19	15
CA 50-32/4T	4	380	DN50	DN32	460	340	h(m)	38	36.5	36	34	32	30	26	21
CA 50-32/5.5T	5.5	380	DN50	DN32	498	340	h(m)	50	49	48	46	45	43	40	29
CA 50-32/7.5T	7.5	380	DN50	DN32	532	340	h(m)	62	60	58	54	52	47	40	35

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (cm)	H (cm)	DEBİ								
							m³/h	5	10	15	20	25	30	35	40
CA 65-40/4T	4	380	DN65	DN40	460	292	h(m)	32	31	30	28	26	24	21	-
CA 65-40/5.5T	5.5	380	DN65	DN40	498	292	h(m)	36	35.5	34	33	31	28	24	20
CA 65-40/7.5T	7.5	380	DN65	DN40	554	360	h(m)	46	45	44	43	41	37	34	30
CA 65-40/10T	10	380	DN65	DN40	592	360	h(m)	52	51.5	51	50	48	45	42	38
CA 65-40/15T	15	380	DN65	DN40	623	360	h(m)	70	69	68.5	68	67	66	64	60

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (cm)	H (cm)	DEBİ									
							m³/h	5	10	20	30	35	40	50	60	70
CA 65-50/4T	4	380	DN65	DN50	455	292	h(m)	26	25	23	20	17	15	10	-	-
CA 65-50/5.5T	5.5	380	DN65	DN50	498	292	h(m)	27	26	25	24	22	20	15	-	-
CA 65-50/7.5T	7.5	380	DN65	DN50	554	360	h(m)	35	35	34	32	30	29	25	-	-
CA 65-50/10T	10	380	DN65	DN50	592	360	h(m)	41	41	40	39	37.5	36	32	28	-
CA 65-50/15T	15	380	DN65	DN50	623	360	h(m)	57	56	55	53	52	51	48	42	30