

KOMPLE PASLANMAZ ÇELİK ÇOK KADEMELİ SANTRİFÜJ POMPALAR

MAX SU SICAKLIĞI : 80°C
MAX ORTAM SICAKLIĞI : 40°C
MAX EMİŞ : 6.5 m



KD.../316 Modeller

Sıvıya Temas Eden Tüm Parçalar
AISI 316 PASLANMAZ ÇELİK

KD... Modeller

Sıvıya Temas Eden Tüm Parçalar
AISI 304 PASLANMAZ ÇELİK

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (mm)	H (mm)	DEBİ										
							m³/h	0	0.5	1	1.5	2	2.5	3	3.5	4	4.5
KD 2-5M	0.75	220	1"	1"	405	236		44	41	39	36	31	28	22	14	4	-
KD 2-6M	1	220	1"	1"	405	236	h(m)	54	52	49	46	43	39	32	24	20	10
KD 2-6T	1	380	1"	1"	405	214		54	52	49	46	43	39	32	24	20	10

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (mm)	H (mm)	DEBİ										
							m³/h	0	1	2	3	4	5	6	7	8	-
KD 4-6M	1.5	220	1¼"	1"	405	236		60	56	54	52	46	43	35	26	15	-
KD 4-6T	1.5	380	1¼"	1"	405	214		60	56	54	52	46	43	35	26	15	-
* KD 4-6M/316	1.5	220	1¼"	1"	405	236	h(m)	60	56	54	52	46	43	35	26	15	-

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (mm)	H (mm)	DEBİ											
							m³/h	0	2	3	4	5	6	7	8	9	10	12
KD 8-2.5M	2	220	1½"	1½"	458	254		52	49	47	46	43	41	37	34	31	27	18
KD 8-2.5T	2	380	1½"	1½"	458	232		52	49	47	46	43	41	37	34	31	27	18
KD 8-4M	3	220	1½"	1½"	500	239		73	70	68	65	61	57	50	48	40	35	20
KD 8-4T	3	380	1½"	1½"	500	232	h(m)	73	70	68	65	61	57	50	48	40	35	20
* KD 8-4M/316	3	220	1½"	1½"	500	239		73	70	68	65	61	57	50	48	40	35	20