



MODEL	GÜÇ		VOLT	BORU GİRİŞ-ÇIKIŞ	MAX.DEBİ (L/min)	MAX. YÜKSEKLİĞİ (m)	MAX. EMİŞ (m)	AĞIRLIK (kg)
	(KW)	(HP)						
HMC-5SC	0.90	1.25	220 V	1"×1"	100	55	6	10.7
HMC-6SC	1.1	1.5	220 V	1"×1"	100	66	6	14.8
HMC-8SC	1.5	2.0	220 V	1"×1"	120	90	6	19.9
HMC-10SC	2.2	3.0	380 V	1"×1"	120	100	6	20.7

POMPA

- Hidrofor Pompası
- Max. Sıvı Sıcaklığı 60°C
- Endüstriyel alanlar ve binalar
- **Paslanmaz mil**
- PPO Fan & Difüzör
- **Temiz Su**

MOTOR

- Monofaze / Trifaze 50hz
- İzolasyon Sınıfı : 130
- Koruma Sınıfı : IP44
- Dış Ortam Sıcaklığı: 40°C
- Termal Aşırı Yük Koruması (M)
- **Bakır Sarma Bobin**

TEMİZ SU

55-100m.

6-8.0 m³/h

Hidrofor Sis.

Part	Material	Remark
1	Mechanical seal	
2	Rotor	Cold-rolled sheet
3	Stator	Aluminum casting
4	Capacitor	High quality
5	End plate	Aluminum
6	Fan	Noryl
7	Fan cover	Iron
8	Pump body	Cast iron
9	Barrel	Stainless steel
10	Impeller	Brass
11	Diffuser	Noryl
12	Bearing	High quality
13	Support	Cast iron

