

DİK MİLLİ ÇOK KADEMELİ PASLANMAZ ÇELİK FANLI POMPALAR

MAX SU SICAKLIĞI : 40 °C
MAX ORTAM SICAKLIĞI : 40 °C
MAX EMİŞ : 6.5 m

* 304 PAS. ÇELİK FANLI
ÇOK SESSİZ



POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	H (mm)	DEBİ									
						m³/h	0	1	2	3	4	5	6	7	-
YKSS 7-4KM	1.5	220	1¼"	1¼"	430	h(m)	50	48	46	42	36	30	22	12	-
YKSS 7-4KT	1.5	380	1¼"	1¼"	430		50	48	46	42	36	30	22	12	-
YKSS 7-6KM	2	220	1¼"	1¼"	514		75	71	70	65	55	48	38	25	-
YKSS 7-6KT	2	380	1¼"	1¼"	514		75	71	70	65	55	48	38	25	-
YKSS 7-8KM	3	220	1¼"	1¼"	562		105	100	95	86	75	60	50	33	-
YKSS 7-8KT	3	380	1¼"	1¼"	562		105	100	95	86	75	60	50	33	-

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	H (mm)	DEBİ									
						m³/h	0	2	4	6	8	9	10	11	12
YKSS 12-4KM	2	220	1½"	1½"	502	h(m)	60	55	50	40	30	25	20	-	-
YKSS 12-6KM	3	220	1½"	1½"	555		90	85	75	60	45	35	25	10	-
YKSS 12-6KT	3	380	1½"	1½"	555		90	85	75	60	45	35	25	10	-
YKSS 12-8KT	4	380	1½"	1½"	668		120	111	96	78	56	44	32	20	5
YKSS 12-10KT	5.5	380	1½"	1½"	718		150	140	123	102	78	65	51	36	20

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	H (mm)	DEBİ									
						m³/h	0	4	6	8	10	12	14	16	18
YKSS 18-4KM	3	220	1½"	1½"	543	h(m)	55	50	48	45	40	35	30	24	18
YKSS 18-4KT	3	380	1½"	1½"	543		55	50	48	45	40	35	30	24	18
YKSS 18-6KT	4	380	1½"	1½"	710		83	75	70	65	60	52	45	35	22
YKSS 18-7KT	5.5	380	1½"	1½"	750		100	90	86	80	70	63	53	42	30
YKSS 18-8KT	6.5	380	1½"	1½"	770		115	103	98	91	82	71	60	50	34